



## P5mm Kinkong Series Technical Specification

P5mm Technical Specification	
Item	Technical Parameter
Pixel Pitch(mm)	5 mm
Pixel Density (dots/m <sup>2</sup> )	40,000 dots/m <sup>2</sup> 16,384 dots/panel
LED Type	SMD 3528
Module size(mm)	320x320mm
Module resolution	64x64
Cabinet Size (mm)	640x640x60 mm
Cabinet resolution	128x128
Cabinet Weight (kg)	9 kg
Driving Method (s)	1/8 s
Brightness (cd/m <sup>2</sup> )	2,000cd/m <sup>2</sup> adjustable by software

# STORMLED

Refresh Frequency(Hz)	$\geq 3000$ Hz adjustable by software
MTBF (H)	>10000 H
Max. Power Consumption(w/m <sup>2</sup> )	600 w/m <sup>2</sup>
View Angle	120°horizontally, 120°vertically
Grey Scale (color)	280 trillion
Color Temperature	R.G.B brightness 256 level adjustable, color temperature is adjustable according to requirements
IP(Protection Index) level	IP 31
Defects Rate	< 1/10000 dots
Life Span (H)	> 100000 H
Operating Voltage	AC220V $\pm 10\%$
Operating Temperature	-20°C ~ +50°C
Operating Humidity	10%RH~90%RH
Certificates	CE ,RoHS